

Push-in plug IV with float housing

Technical data



for: T 54 62mm / 2.13...2.23"
 T1 = 58mm / 2.13"
 T2 = 38mm / 1.50"

applicable for cell depth
 (T) 584....58mm / 2.13...2.23"

(T = top of cell to top of separator)

Filling level (T2) 38mm / 1.34"

(T2 = max. filling level,
 top of cell to top of electrolyte level)

for: T 58 62mm / 2.23...2.44"
 T1 = 58mm / 2.13"
 T2 = 38mm / 1.50"

applicable for cell depth
 (T) 58....62mm / 2.23...2.44"

(T = top of cell to top of separator)

Filling level (T2) 38mm / 1.50"

(T2 = max. filling level,
 top of cell to top of electrolyte level)

for: T 62 66mm / 2.44...2.60"
 T1 = 62mm / 2.44"
 T2 = 42mm / 1.65"

applicable for cell depth
 (T) 62....66mm / 2.44...2.60"

(T = top of cell to top of separator)

Filling level (T2) 42mm / 1.65"

(T2 = max. filling level,
 top of cell to top of electrolyte level)

for: T 66 70mm / 2.60...2.76"
 T1 = 66mm / 2.60"
 T2 = 46mm / 1.81"

applicable for cell depth
 (T) 66....70mm / 2.60...2.76"

(T = top of cell to top of separator)

Filling level (T2) 38mm / 1.81"

(T2 = max. filling level,
 top of cell to top of electrolyte level)

for: T > 70mm / > 2.76"
 T1 > 70mm / > 2.76"
 T2 = 50mm / 1.97"

applicable for cell depth
 (T) > 70mm / > 2.76"

(T = top of cell to top of separator)

Filling level (T2) 50mm / 1.97"

(T2 = max. filling level,
 top of cell to top of electrolyte level)